

KY TYPE 70





d	D	D1	L1	L2
15	31.5	29.5	8	18/24
16	31.5	29.5	8	18/24
20	37	35	5	15
25	44.2	40	5.5	16.5
30	48.6	45	6	18
35	54	50	6.5	19.5
40	60.4	58	7.5	20.5
	15 16 20 25 30 35	15 31.5 16 31.5 20 37 25 44.2 30 48.6 35 54	15 31.5 29.5 16 31.5 29.5 20 37 35 25 44.2 40 30 48.6 45 35 54 50	15 31.5 29.5 8 16 31.5 29.5 8 20 37 35 5 25 44.2 40 5.5 30 48.6 45 6 35 54 50 6.5

Elastomer Bellow Shaft Seals

Combined Materials

- Stationary Ring (Ceramic/SiC/TC)
- Rotary Ring (Carbon/SiC/TC)
- Secondary Seal (NBR/EPDM/Viton)
- Spring and Punched Parts (Steel)

Working Conditions

- Pumps: Submersible pumps and common multi-stage deep well pumps.
- Temperature: -20°C~110°C
- Pressure: ≤0.8MPa
- Speed: \leq 10 m/Sec
- Add: No. 7 Mingshu Road, Jiangshan Town, Ningbo, Zhejiang, China, 315191
- Tel: +86-134-56162828
- +86-138-67856735